



| Specification Description | Specification | Notes |
|--|-----------------------|---|
| Battery | 24 VDC (Rechargeable) | |
| Amps Mobilette | 5.2A | 9A Wide |
| Amps Wall Charger | .5A | |
| Duty | 10% Initial | 1 Min. On / 9 Min Off |
| Nominal Charging Time Of Battery | Usually Over-night | If the Charging Time is Longer Than 20 Hrs., the Charger or Battery is defective. |
| Casters Front | 3" Non-Brake | Except on Pacific and EO Transfers |
| Casters Rear | 4" Braked | Pacific Chair and EO Has 2 Non-Braked also. |
| Minimum Clearance From Bottom of Seat to Floor | 16" | Varies From Transfer to Transfer, and is Adjustable |
| Maximum Clearance From Bottom of Seat to Floor | 39 1/2" | Varies From Transfer to Transfer, and is Adjustable |
| Adjustable Clearance | 2" | |
| Scale Increments Standard | .5 Lbs. | |
| Scale Increments Wide | 1 Lbs. | |
| Raising Time Lowest to Highest Empty | Less Than 30 Seconds | Slight Difference in Wide and Stretchers |
| Lowering Time Highest to Lowest Empty | Less Than 30 Seconds | Slight Difference in Wide and Stretchers |
| Scale Readout Batteries | AA 1.5VDC | Located Bottom of Readout |
| Stroke Length Superior and Cascade | 23 1/2" | |
| Stroke Length Stretcher | 20" | |
| Stroke Length Wide | 12" | |
| | | |